



To be the leading supplier of engineering transportation solution and equipment

TONLY

**OFF-ROAD DUMP
TRUCK**



TONLY OFF-ROAD DUMP TRUCK

» Cabin

- The new cab has a spacious interior.

» High Reliability

- Adopting a high-power engine and a reinforced mine specific gearbox. The flexible frame with core technology has strong ability to absorb and attenuate impacts. A brand new axle with strong load-bearing and braking capabilities.



To be the leading supplier of engineering transportation solution and equipment



» **High Payload Capacity**

- Large single vehicle payload and high overall efficiency.

» **High Safety**

- Anti-collision beam+ Anti-roll frame rigid cab+ Through beam type bumper



MAIN PRODUCT CONFIGURATIONS AND TECHNICAL PARAMETERS

Drive Mode	6x4
Kerb Weight (kg)	16800
Payload (kg)	32170
GvW (kg)	50000
Dimensions(mm)	8830 x2510 X3550
Max speed (km/h)	55
Min.Ground Clearance(mm)	285
Min. turing radius (m)	≤10
Max. Climbing degree (%)	30
Wheelbase(mm)	3775+1400
Cab	Single rigid right side cab, hydraulic seat, built-in air conditioning, sliding windowglass manual reverse.

Right Cabin +7DS180

Engine	Weichai WP10.380E22 / Yuchai YC6MK375-33
Gearbox	7DS180 with PTO QH70
Front axle	MAN 9.5 Ton
Rear axle	MAN 16+16 TON, speed ratio: 6.733
Chassis	850x320(8+7+8)
Suspension	Leaf spring (with Cross stablizer bar + shock absorber)
Fuel tank	Iron tank 400L
Size of tire	10+1/12.00R20
Size of cargo body(mm)	U type 21 CBM with tailgate
Thickness of plate	Bottom 10 mm , front & side & tailgate 8 mm
Lifting system	HYVA 157
Other devices	Metal bumper, desert air filter, water tank guardrear bumper, 165Ah maintenance free battery

Left Cabin +10JSD180T

Drive Mode	6x4
Kerb Weight (kg)	16800
Payload (kg)	32170
GvW (kg)	50000
Dimensions(mm)	8830 x2510 X3550
Max speed (km/h)	55
Min.Ground Clearance(mm)	285
Min. turing radius (m)	≤10
Max. Climbing degree (%)	30
Wheelbase(mm)	3775+1400
Cab	Single rigid left side cab, hydraulic seat, built-in air conditioning, sliding windowglass manual reverse.

Engine	Weichai WP10.380E22 / Yuchai YC6MK375-33
Gearbox	10JSD180T with PTO QH50
Front axle	MAN 9.5 Ton
Rear axle	MAN 16+16 TON, speed ratio: 6.733
Chassis	850x320(8+7+8)
Suspension	Leaf spring (with Cross stablizer bar + shock absorber)
Fuel tank	400L
Size of tire	10+1/12. 00R20
Size of cargo body(mm)	U type 21 CBM with tailgate
Thickness of plate	Bottom 10 mm , front & side & tailgate 8 mm
Lifting system	HYVA 157
Other devices	Metal bumper, desert air filter, water tank guardrear bumper, 165Ah maintenance free battery

"Zero distance" warmhearted service

"Zero distance" warmhearted service



Object:


Create the first service brand of wide-body dump truck

Commitments:

The equipment attendance rate within warranty period is not lower than 90%

"Specialized" training


The operation training, maintenance training, management personnel training, safety training and special trainings are organized and implemented exclusively.



"2123-3" service response mechanism

- 2** Arrive at side in 2h
- 1** Solve common fault in one day
- 2** Offer solution for special fault in 2 days
- 3** Solve major fault in 3 days
- 3** 3. Arrival: the service personnel, accessory and trainers arrive at the construction site together with the vehicle.

Technical Support



Technical Hotline
029-38001222

Service Hotline
029-38001210 400-6863853

To be the leading supplier of engineering transportation solution and equipment

| Application Cases





TONLY VALUE SHARING WITH THE WORLD



Shaanxi Tonly Heavy Industries Co., Ltd.

Address: No. 2339, Fengchan Road, Fengdong New Town, Xi 'an City, Shaanxi Province

Sales Hotline: 029-38001214 Service Hotline: 029-38001210 400-6863853

E-mail: tonly2010@yeah.net Website: www.sntonly.com

TONLY reserves the right of design modification and interpretation.

All parameters and details are subjected to the business contract and commercial vehicle

DISTRIBUTED BY:



AIRINDO SAKTI

www.airindosakti.co.id